

E1480W Specification

Effective Image Sensor Pixels	14.1 Megapixels	
Image Sensor	14.2 Megapixels [1/2.3" Charge Coupled Device (CCD)]	
Lens	Focal Length F =	5.1 mm (Wide) — 40.8 mm (Tele)
	[35mm film equivalent	[28 mm (Wide) — 224 mm (Tele)]
	F number	f / 3.3 (Wide) — f / 5.8 (Tele)
	Lens Construction	12 elements in 8 groups
	Optical Zoom	8x
	Focusing Range	Normal: (Wide) 23.6 in. ~ ∞ / 60 cm ~ ∞ , (Tele) 39.4 in. ~ ∞ / 100 cm ~ ∞ Macro: (Wide) 2.0 in. ~ 39.4 in. / 5 cm ~ 100 cm, (Tele) 39.4 in. ~ ∞ / 100 cm ~ ∞
Anti-Handshake	Optical Image Stabilization	
Digital Zoom	6x Digital Zoom (Combined Zoom: 48x)	
Number of Recording Pixels	Still Image	14MP: 4320×3240, (3:2) 12MP: 4320×2880, (16:9) 10MP:4320×2430 8MP: 3264×2448 , 5MP: 2592×1944, 3MP: 2048×1536, 2MP: 1920×1080, 0.3MP: 640×480
	Movie	1280×720 pixels: 30 fps / 15 fps, 640×480 pixels: 30 fps / 15 fps, 320×240 pixels: 30 fps / 15 fps
Image Compression	Best, Fine, Normal	
DCF, DPOF (Ver1.1) Support	Yes	
File Format	Still Image	Exif 2.2 (JPEG)
	Movie	Movie Format: MPEG-4, Audio: mp2
	Audio	WAVE [Monaural] (Max 60 seconds)
Shooting Modes	Auto, Manual, ASCN, Portrait, Scene (Sport, Landscape, Children, Indoor, Leaf	
	Snow, Sunset, Fireworks, Glass, Museum, Night Landscape, Night Portrait), Panorama, Movie	
Detection Features	Face, Smile, Blink	
Red-eye Removal	Yes	
LCD Display	3.0 inch (230,400 pixels) TFT-LCD	
	Auto Adjust Brightness LCD	
ISO Sensitivity	Auto, ISO 80 / 100 / 200 / 400 / 800 / 1600 / 3200	
AF Method	Single AF, Multi-AF (TTL 9-point), Face-Detection+AE, AF Assist Light (On / Off)	
Exposure Metering Method	Artificial Intelligence AE (Ai AE), Center-weighted Average, Spot (Fixed to center of frame)	
Exposure Control Method	Program AE (AE-lock available)	
Exposure Compensation	± 2 EV in 1/3 Step increments	
Shutter Speed	4 ~ 1/2000 seconds (Manual: 30 seconds)	
Continuous Shooting	Approx. 1.39 fps (Large / Fine Mode)	
Playback Modes	Single Photo, Index (4 / 9 / 16 thumbnails), Slide Show, Movie (Slow-Motion possible)	
	Zoom (Approx. 2x ~ 8x), Audio, Histogram Display	
White Balance Control	Auto (AWB), Daylight, Cloudy, Fluorescent, Fluorescent CWF, Incandescent, Manual	
Internal Flash (Shooting Range)	Auto, Red-Eye Reduction, Forced Flash, No Flash, Slow Synchro, Red-Eye Reduction + Slow Synchro	
	Gno. 6.3 (ISO 100) D=1.5m	
	Shooting Range: (Wide) Approx. 11.8 in. ~ 212.6 in. / 0.3 m ~ 5.4 m (Tele)-Approx. 11.8 in. ~ 122.0 in. / 0.3 m ~ 3.1 m (ISO 800)	
Recording Media	Internal Memory: 18 MB	
	SD Card / SDHC Card (Up to 16 GB support)	
Other Features	PictBridge, ExifPrint Support, Multi-language Support (26 Languages)	
Jacks	USB2.0 / AV-OUT (Integrated Proprietary Connector), HD OUT	
Power	Rechargeable Lithium-ion Battery GB-10 (D016) , 3.7V 700mAh	
Shooting Capability (Battery Performance)	Approx. 160 shots (based on CIPA Standards)	
Operation Environment	Temperature: 32 ~ 104 F / 0 ~ 40°C, Humidity: 0 ~ 90%	
Dimensions (W x H x D)	3.9 in. × 2.3 in. × 0.8in. ~ 1.0 in. / 98.3 mm × 56.8 mm × 19.5 mm ~ 24.4 mm	
Mass	Approx. 4.8 oz. / 135 g (Body only)	
Supplied Accessories	Rechargeable Lithium-ion Battery, Battery Charger, USB Cable	
	AV Cable, Wrist Strap, CD-ROM, Manual	
	Quick Start Guide, Feature Guide, Warranty Card	