

E Series

E1050



With all its advanced features, this camera gives you great pictures with just a touch.

Compact and stylish, the GE E1050 redefines the term "feature-rich." For starters, it offers the latest touch-screen panel technology that makes it fun and easy to take fabulous photos. Plus, the aspheric all-glass lens provides an ultra sharp image. The E1050 is our first camera to offer direct HDTV output, plus an optional GPS accessory.

With a spacious 3-inch high-resolution LCD screen (230,400 pixels), photo playback is a delightful experience. The GE E1050 comes with the latest auto-brightness LCD technology that ensures perfect screen visibility both indoors and outdoors.

Featuring a comprehensive 10-megapixel resolution, 5x optical zoom, 4.5x digital zoom, 22.5x combined zoom, and a 28mm wide angle lens, you won't find a camera that's more versatile ... from tight close-ups to wide group shots.

Within the 23.5mm slim body design is a host of advanced features, including: In-Camera Panorama Stitching, Smile Detection, Blink Detection, Face Detection, Electronic Image Stabilization, Red-Eye Removal and an amazing 1280x720 MPEG-4 movie recording capability.

Hold the E1050 and see for yourself all it has to offer. Then you'll understand how this camera is taking point-and-shoot models to a whole new level.

Shown in black.
Also available:



Red



Silver



With all its advanced features, this camera gives you great pictures with just a touch.

Effective Image Sensor Pixels	10.5 Megapixels	
Image Sensor	10.7 Megapixels [1/2.33" Charge Coupled Device (CCD)]	
Lens	Focal Length F =	5 mm (Wide) — 25 mm (Tele)
	[35mm film equivalent]	[28 mm (Wide) — 140 mm (Tele)]
	F number	F3.3 (Wide) — F4.9 (Tele)
	Lens Construction	9 elements in 8 groups
	Optical Zoom	5x
Focusing Range	Normal	: 60cm~∞
	Macro	: (Wide) 5cm~∞
Anti-Handshake	Electronic Image Stabilization	
Digital Zoom	4.5x digital zoom (Combined Zoom: 22.5x)	
Number of Recording Pixels	Still Image	10MP: 3648×2736, (3:2)9MP: 3648×2432, (16:9)7MP: 3648×2052, 5MP: 2560×1920, 3MP: 2048×1536, 2MP: 1600×1200, 1MP: 1024×768, 0.3MP: 640×480
	Movie	1280×720pixels: 30fps, 640×480pixels: 30fps/15fps, 320×240pixels: 30fps/15fps
Image Compression	Best、Fine、Normal	
DCF、DPOF (Ver1.1) Support	Yes	
File Format	Still Image	Exif2.2 (JPEG)
	Movie	Image Compression: MPEG4, Audio: G.711 (Monoaural)
	Audio	WAVE [Monoaural] (Max 60 seconds)
Shooting Modes	Auto, Manual, Image Stabilization, Movie, Scene (Sport, Children, Indoor, Leaf, Snow, Sunset, Fireworks, Glass, Museum, Landscape, Night Landscape, Night Portrait), Panorama, Portrait	
Start-Up Time	1.5 sec.	
Detection Features	Face, Smile and Blink	
Red-Eye Removal	Yes	
GPS Support	Yes	
Viewfinder	-	
LCD Screen	3.0 inch (230.400 pixels) LTPS (low-temperature polycrystalline silicon) TFT color LCD Self-regulation brightness in the sun	
ISO Sensitivity	Auto, ISO80/100/200/400/800/1600/3200	
AF Method	Single AF, Multi-AF (TTL 9-point), Face-Detection, AF Assist Beam (On / Off)	
Light Metering Method	Artificial Intelligence AE (Ai AE), Center-Weighted Average, Spot (Fixed to center of frame)	
Exposure Control Method	ProgramAE (AE-lock available)	
Exposure Compensation	± 2 EV in 1/3 Step increments	
Shutter Speed	4 ~ 1/2000 second (Manual 30s)	
Continuous Shooting	Approx. 1.8 fps (Large/Fine Mode)	
Playback Modes	Single Photo, Index (4 / 9 / 16 thumbnails), Slide Show, Movie (Slow-Motion possible), Zoom (Approx. 2x~8x), Audio , Histogram Display	
White Balance Control	Auto (AWB), [Daylight, Cloudy, Incandescent, Fluorescent, Fluorescent CWF , Manual]	
Internal Flash (Shooting Range)	Auto / Red-Eye Reduction / Forced Flash / No Flash / Slow Synchro / Red-Eye Reduction+Slow Synchro	
	Shooting Range Wide: Approx. 0.3m~3.2m / Tele: Approx. 0.3m~2.1m (ISO 400)	
Recording Media	Internal Memory: 26MB	
	SD Card / SDHC Card (Up to 4GB support)	
Other Features	PictBridge、ExifPrint Support、Multi-language Support (11 languages)	
Jacks	USB2.0 / AV-OUT (Integrated Proprietary Connector), HDTV	
Power	Rechargeable Lithium-ion Battery GB-40, 3.7V 1050mAh	
Shooting Capability (Battery Performance)	Approx. 200 shots (based on CIPA Standards)	
Operation Environment	Temperature: 0~40°C, Humidity: 0~90%	
Body Material	Metal cover	
Dimensions (W x H x D)	3.6 inch Width × 2.2 inch Height × .9 inch Depth (92.5mm Width × 57mm Height × 23.5mm Depth)	
Weight	5.1 oz. (Approx. 145g) (Body only)	
Supplied Accessories	Rechargeable Lithium-ion Battery, Battery Charger, USB Cable, AV Cable, Wrist Strap, CD-ROM, Manual, Quick Start Guide, Warranty Card	